

GE239 & GE242 Product Information

When a mechanical pump fails in older vehicles it can be very hard and expensive to replace, in some cases the part may be no longer available. The release of GE239 and GE242 is an economical solution to this problem. Available in two specifications that suit a wide range of petrol and diesel powered vehicles. Each pump comes with fitting instructions and accessories

Applications

- ✓ On carburetted vehicles with 12 volt electrical systems
- ✓ As a diesel lift/feed pump on vehicles with 12 volt electrical systems

Features and Benefits:

- ✓ Compact, easy to fit - includes inlet filter and hose fittings
- ✓ Can be used with both positive and negative ground electrical systems
- ✓ Solid state electronics
- ✓ Low power requirement - approximately 1 amp at maximum delivery
- ✓ Compatible with all fuel types except methanol
- ✓ Self-priming
- ✓ Built-in pressure relief

Fitting:

- * The pump should be mounted as close to the fuel tank as possible
- * The pump must be mounted no more than 305 mm above the bottom of the fuel tank

	Voltage	Max. Dry Suction Lift		Max. Pressure		Max. Flow	
	V	in	mm	psi	kPa	(imp) gph	l/h
GE239	12	12	305	4.5 - 6	31 - 41	34	129
GE242	12	12	305	3 - 4.5	21 - 31	30	114

