Working voltage: DC 12V Only

Types of LED: 5050 SMD RGB

Frequency band: 2.4GHZ

Bluetooth distance: No obstacle 30ft



Instruction Manual

PACKAGE CONTENTS



4 v Multi-Color Micro LED Light



3M™ double-sided tane



4 x 24" Extension

36" Power Cable with 12V Hardwire Power Adapter


TECHNICAL SPECIFICATION

Plug & Glow™

Smart Lighting **Hub Controller**

Maximum LED: 72 Micro Lights Maximum amperage draw: 3A


INSTALLATION



- · Choose your desired location (- see suggestions above)
- · Clean surface thoroughly with
- isopropyl alcohol. Dry completely.
 Peel off the 3M™ tape backer and carefully apply to the desired area.

• For use with 12V power only Suitable temperature for installation is 70°F (21°C) or above.


POWER



Two Power options available
212V Plug-in power adapter **©**12V Hardwire

1) Select your desired power connection and connect to the Plug & Glow™ Smart Lighting Hub Controller Connect LED strip with extension cable

to the Smart Lighting Hub Controller. Use arrow indication to match the correct direction.



APP INSTALLATION



Install Smart Lighting APP on your Smart phone. Scan above QR code to find the compatible APP for iOS or Android.

· Or you can search for the APP through the APP Store or Google Play by:



APP and begin enjoying vour Plua & Glow™ experience.



Tap "Smart LED Hub" Icon to start

USING THE APP

Home Page



APP will automatically pair to the Hub when both are powered on (including Bluetooth) and within 30ft



A Master On/Off Switch

Connect and control up to four

On/Off: Press each zone icon to turn

Press and hold zone icon, select

Press and hold zone icon, select

"Rename" to rename each icon.

You can select multiple zones and

control the same setting at once.

Press and hold zone icon, select

"Select Multiple" then select your

desired zone by pressing "Confirm"

To ungroup your selection, press and

hold zone icon and select "Ungroup"

Press>, select your desired vehicle

Select Vehicle Schematic:

(Note: Maximum 4 characters).

"Move" to position each zone icon at

B LED Zone Functions:

separate zones

LED On or Off.

Move Zone Icon:

vour desired location.

Rename Zone Icon:

Select Multiple:

schematic.





24"

C Save Preset: You can save your favorite settings. After creating your setting, press "Save Preset" and enter your preset name. You can save up to 10 preset settings.

Select Preset:

You can select your previously saved preset setting, press "Select Preset and choose your saved setting.

Delete Saved Preset Setting:

To delete a saved preset setting, press "Select Preset" and press and hold the preset setting that you wish to delete. Press "Yes" to delete.

Select Color:

Choose from up to 49 different colors. Press "Select Color", select your desired color and press

D LED Mode: Choose from 8 different modes Note: Music Mode is sound activated.

Brightness:

ide bar to adjust brightness setting


Slide bar to adjust the speed of the movement from each LED Mode.

EXTENDABLE

Type S Plug & Glow™ kits can be extended up to maximum of 20ft (6m) using compatible extension strips.

To function properly extension strips must be connected to the same type of strip. (see examples below)





Plug & Glow Red/ Blue/ White + Multi color Extension

Extend up to a

or injury to persons. 5. To reduce risk of damage to cigarette lighter connector and cord, pull by Multi color + Multi color Micro Light Extension cigarette lighter connector rather than cord when disconnecting LED kit.

I M55391

or snow

6. Make sure cord is located so that it will not be stepped on, tripped over, or otherwise subjected to damage or stress.

WARNING

IMPORTANT SAFETY INSTRUCTIONS

1. SAVE THESE INSTRUCTIONS- This

manual contains important safety and

2. Before using this LED kit, read all

instructions and cautionary markings.

3. Do not expose LED kit to rain, moisture,

4. Use of an attachment not recommended

or sold by the battery LED kit manufacturer

may result in a risk of fire, electric shock,

operating instructions for LED kit Model

7. Do not operate with damaged cord or cigarette lighter connector - replace it immediately

8. Do not operate LED kit if it has received a sharp blow, been dropped, or otherwise. damaged in any way; take it to a qualified

9. Do not disassemble LED kit; take it to a qualified serviceperson when service or repair is required. Incorrect reassembly may result in a risk of electric shock or fire.

10. To reduce risk of electric shock, unplug charger before attempting any maintenance or cleaning. Turning off controls will not reduce this risk.

11. Make sure cord is located so it will not be stepped on, tripped over, or otherwise subjected to damage or stress.

4PC Plug & Glow™ Micro Lights Smart LED Kit LM55391 Responsible Party: Winplus North America Inc

2975 Red Hill Ave., Ste. 100, Costa Mesa, CA 92626, USA Tel: 1-866-294-9244

FCC / IC Compliance Statement:

This device complies with Part 15 of the FCC rules and Industry Canada Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accent any interference received, including nterference that may cause undesired operation.

NOTE: This equipment has been tested and found to comply with the limits for Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide

interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions. may cause harmful interference to radio or elevision reception, which can be determine by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

reasonable protection against harmful

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and the receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help. The device has been evaluated to meet

general RF exposure requirement. To maintain compliance with FCC/IC's RF exposure guidelines, this equipment should be installed and operated with a minimum distance of 20cm between the radiator and your body.

CAN ICES-3 (B)/NMB-3(B)

▲ WARNING: This product can expose you to chemicals including DEHP and DINP. which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

? Have a comment or question? Email us at: info@typesauto.com or visit us online at: www.tvpesauto.com

Winplus North America, Inc. 2975 Red Hill Ave., Ste. 100, Costa Mesa, CA 92626 Tel: 1 866 294 9244 © 2019 Winplus North America, Inc. All rights reserved. 3M™ is a trademark of 3M Company.

Apple, the Apple logo, iPhone, iPad, and iPod touch are trademarks of Apple Inc. App store is a service mark of Apple Inc. Android, Google Play, and the Google Play logo are trademarks of Google Inc.

OPTIONAL ACCESSORIES

Optional Smart LED products also available to enhance your experience (sold separately)



48" Smart Lighting Deluxe Kit



72" Exterior Smart Lighting Kit

ML-55391 V2

RONT