

**MATSON**

# 12V BATTERY MONITOR



**MA98416**



# 12V BATTERY MONITOR

## INTRODUCTION



- 1 Voltage indicating LED's
- 2 Positive Terminal (Red)
- 3 Negative Terminal (Black)



# 12V BATTERY MONITOR

## INSTALLATION

Positive Terminal  
(Red)



Negative Terminal  
(Black)

1. Firmly attach the Negative (black) connector to the Negative battery terminal
2. Firmly attach the Positive (Red) connector to the Positive battery terminal
3. Mount the device to the battery surface



**SCAN ME**  
For installation and  
operation video





# 12V BATTERY MONITOR

## OPERATION

Simply observe the LED indicators, as the voltage increases or decreases the lights will indicate the current voltage range.

Recharge the battery as required.

## WARRANTY

Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and for compensation for any other reasonably foreseeable loss or damage incurred if the product fails when used for the purpose for which it was intended. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.

The warranty is given by:

Tridon Australia, 21-25 Derby St, Silverwater, NSW 2128.

Tel: 1300 362 263

Email: [mail@tridon.com.au](mailto:mail@tridon.com.au)