



100 Celebrating YEARS

AUSTRALIAN OWNED AND TRUSTED SINCE 1926 

PRO GEAR GL-5 75W-85 (100% PAO ESTER)

Last updated: 18/03/2025 2:45 pm

PRODUCT CODE	PACK SIZE	CARTON QTY
PROGL50025	2.5L	4
PROGL5020	20L	
PROGL5060	60L	

PRODUCT BENEFITS

Pro Gear GL-5 75W-85 is a premium full synthetic, SAE 75W-85, differential and transaxle gear oil heavy duty gear oil manufactured with **100% PAO ESTER** synthetic base oils, with an advanced additive system to provide the ultimate performance and protection under all operating conditions. It meets the performance requirements of API GL-5 as well as many manufacturers specifications.

APPLICATION

Pro Gear GL-5 75W-85 is optimised for use in both hypoid and limited slip differentials, transfer cases, manual transaxles and gearboxes in late model passenger cars, 4WD's and light commercial vehicles that specifically require the use of an API GL-5, SAE 75W-85 viscosity gear oil.

Pro Gear GL-5 75W-85 is suitable for use where MB 235.31, MB 235.62, MB 235.7, ZF TE-ML 18 is specified and where VW TL 521 45-X is required. Suitable for use in BMW, Toyota, Lexus, Ford, GM/Holden, Land Rover, Chrysler & Jeep vehicles requiring this viscosity and specification. It may be used in selected manual transmissions that require a SAE 75W-85 viscosity grade with API GL-5 specifications and can be used to improve shift quality in colder climates where either SAE 75W-90 or SAE 80 API GL-5 oils are specified.

Pro Gear GL-5 75W-85 85 is already dosed with the correct amount of friction additive for use in limited slip differentials, no extra additive is required.

NOTE: For manual gearboxes requiring an API GL-4, SAE 75W-85 viscosity gear oil, we recommend [Penrite Pro Gear 75W-85](#). **Pro Gear GL-5 is NOT a replacement for Pro Gear 75W-85**

PRODUCT BENEFITS

- **100% PAO ESTER** base oils for ultimate performance,
- **OUTSTANDING** protection and longer life
- **OPTIMISED** for differentials requiring low viscosity API GL-5 fluid.
- **SUITED** to many late model vehicle requirements
- **INCREASED** oxidation stability, reducing harmful deposits
- **ENHANCED** wear protection additive pack
- **SUITABLE** for use in hypoid and limited slip differentials
- **PROVIDES** fuel saving benefits over standard differential oils

PRODUCT PERFORMANCE LEVELS

- API GL-5

TYPICAL DATA

Colour	Amber
Density at 15°C, kg/L	0.880
Viscosity, Kinematic, cSt at 40°C	74
Viscosity, Kinematic, cSt at 100°C	11.4
Viscosity Index	166
Viscosity, Brookfield, cSt @ -40°	36,800
Phosphorus, Mass %	0.140

