



100 Celebrating YEARS

AUSTRALIAN OWNED AND TRUSTED SINCE 1926



PRO SERIES EGR & CAT CLEAN +

Last updated: 05/09/2025 1:19 pm

PRODUCT CODE	PACK SIZE	CARTON QTY
PSECC0005	500ml	6

PRODUCT BENEFITS

EGR & CAT CLEAN+ is a new generation, low volatility, professional automotive cleaning product that effectively cleans and prevents build-up of deposits that block emission control devices such as catalytic converters and exhaust gas recirculation (EGR) systems. It contains non-flammable ingredients that will pass through to the exhaust cycle and clean these components.

APPLICATION

EGR & CAT CLEAN+ is designed for use in all 4, 6 & 8+ cylinder, multi cam, multi-valve including VVT, naturally aspirated, supercharged & turbocharged engines. It can be used in high performance and standard engines as well as in competition and normal on/off road use. It is not suitable for use in 2 Stroke engines.

EGR & CAT CLEAN+ cleans deposits from intake valves, fuel injectors and combustion chambers for easier starts, faster acceleration, better airflow and increased efficiency. It cleans and prevents harmful deposits forming in catalytic converters, cleans EGR passageways with regular use and also cleans oxygen sensors for smoother idling and running.

HOW TO USE

USE ONLY AS DIRECTED ON VEHICLES IN SOUND MECHANICAL CONDITION

NORMAL FUEL ADDITIVE USE

- For routine and preventative maintenance, add **EGR & CAT CLEAN+ (ECC+)** directly to the fuel at a dosage rate of approximately 2-3%. Run the engine to normal operating temperature and then for a further 10 minutes to clean the internals of the fuel pump, the fuel injectors or carburettor, the spark plugs where fitted, and the top piston rings. It will also remove any condensed water from these parts of the system. Due to the low flammability of **ECC+**, do not add to the fuel tank with lower than 15 Litres of fuel and do not add directly into fuel filter.
- The can is a one-dose system. Empty the entire can into approximately 20-25 litres of fuel to enable it to remain concentrated as it goes through the cycle. Normally one treatment is sufficient to clean the system.

SERVICE MAINTENANCE - FOR PROFESSIONAL USE ONLY

- For more intense cleaning of the O2 sensor, exhaust gas recirculation valve, catalytic converter or particulate filter; connect a flexible tube with a tap (e.g. vacuum pipe) from the inlet manifold into the can of **ECC+**. Alternatively, the product can be poured directly into a pump spray bottle and sprayed directly into the vacuum pipe.
- Run the engine at approx. 2000 to 3000 RPM and open the tap or commence spraying at short intervals to draw the product into the areas where it will start to work and give the above benefits. The engine could stall – this is because **ECC+** is not a fuel. If the engine speed drops sharply i.e. below 700 RPM, close the tap or stop the spray and reduce the application speed or increase the interval between applications. This signifies that the product is starting to do its job.
- Leave the **ECC+** in the system and remove the can of **ECC+** and reconnect the vacuum pipe.
- Turn the engine over until it starts – this may take several minutes as the **ECC+** is replaced by fuel from the fuel tank. The unburned **ECC+** will pass the O2 sensor and clean it. It will also clean the exhaust gas recirculation valve, catalytic converter and particulate filter.
- Procedures 2-4 may be repeated to ensure sufficient product is drawn into the system to treat all the components.

VEHICLE & FUEL TYPES

EGR & CAT CLEAN+ is suitable for use in passenger cars and light commercial vehicles and can be used with vehicles running on Petrol/LPG, and E10. Suitable for use in Hybrid vehicles.





100 Celebrating
YEARS

**AUSTRALIAN OWNED AND
TRUSTED SINCE 1926** 

PRODUCT BENEFITS

- Powerful low cost alternative to costly repairs
- Reduces exhaust emission
- Increases engine performance and improves fuel economy
- Removes deposits from injectors, reducing misfire events
- Cleans catalytic converters, reducing harmful build up
- Cleans EGR passageways with continued use
- Cleans oxygen sensors to smooth rough idling
- Reduces CO, HC, and NOx emissions
- Compatible with petrol/LPG and E10 fueled engines.

PRODUCT PERFORMANCE LEVELS

TYPICAL DATA

Colour	Blue
Flash Point, °C	67