



World's
Strongest
Bond™

TankWeld™

Strength 4000 PSI

Set Time 5 Minutes

Cure time 1 Hour

Cure Color Dark Grey

Fuel Resistant
Epoxy Putty

GREAT FOR:

- Fuel Tanks
- Metal Tanks
- Potable Water Tanks
- Lawn & Garden Equipment
- Metal Surfaces
- No Welding
- Ethanol Resistant
- Chemical Resistant



Drinking
Water Safe



Made in USA

NET WT. 2.0 OZ. (57 g)



TankWeld™

Petroleum Resistant **Epoxy Putty**

31023

About TankWeld™

TankWeld™ is a hand-mixable, steel-reinforced, non-rusting epoxy putty that quickly repairs or rebuilds anything made of metal. After mixing, it forms an industrial-strength polymer compound that can be molded into shapes or used to build up, patch and repair steel components. TankWeld™ sets in 5 minutes and after 60 minutes, can be drilled, tapped, machined, ground, filed and painted. TankWeld™ cures to a dark grey color, is rated at a strength of 4000 PSI and will withstand temperatures up to 148°C.

INSTRUCTIONS

- 1 Cut:** Remove required amount of putty.
- 2 Mix:** Wear gloves. Thoroughly knead putty with fingers to a uniform color.
- 3 Apply:** Press putty firmly to the surface to be repaired.

** For best results use a detergent or degreaser to first clean the surface, then roughen surface with file or coarse sandpaper to provide the best repair.*

Australia Contact Information

J-B Weld® Distributor: HPP Lunds

Address: 1/195 Jackson Rd
Sunnybank Hills
Qld 4109

Telephone: 1300 306 781

New Zealand Contact Information

J-B Weld® Distributor: Griffiths
Equipment Ltd

Address: 22-24 Olive Rd
Penrose, Auckland
New Zealand 1061

Telephone: + 64 9 5254575

SAFETY DIRECTIONS

Avoid eye contact. Wear eye protection.
Avoid skin contact. Wear protective gloves.
Avoid breathing dust or vapour.

FIRST AID

For advice in an emergency:

In Australia: contact a Poisons
Information Centre 13 11 26

In New Zealand: contact NZ Poisons
Centre 0800 POISON (0800 764766) or a
doctor at once.

INHALATION: Remove affected person
from area. Keep at rest until recovered. If
symptoms persist seek medical attention.

INGESTION: Do not induce vomiting.
Wash out mouth with water. Seek
medical attention.

SKIN: Wash area with soap and water.
If symptoms develop, seek medical
attention.

EYE: If in eyes, hold eyelids apart and
flush continuously with running water.
Remove contact lenses. Continue
flushing for several minutes until washed
out completely. If symptoms persist, seek
medical attention.

CAUTION

KEEP OUT OF REACH OF CHILDREN.
DO NOT SWALLOW.
READ SAFETY DIRECTIONS BEFORE USING.
TOXIC TO AQUATIC LIFE.
CONTAINS AMINES AS CURING AGENTS
FOR EPOXY RESIN 15-25%.
Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
Toxic to aquatic life.



DRINKING WATER SAFE



0 43425 61217 5

J-B Weld Company
P.O. Box 483
Sulphur Springs,
TX U.S.A. 75483

For more information visit:

www.jbweld.com

Made in USA

Product No.
8217AUS